





















All-in-One with Automatic Duplex Feature

MFC-8860DN doubles your efficiency with its Automatic Duplex: Featuring double-sided printing, faxing, copying and scanning for time and resource savings!

MFC-8860DN comes with duplex printing that allows printing on both sides of the paper, giving you the luxury of producing professional looking documents like booklets, newsletters and brochures.

In addition, the built-in Duplex Automatic Document Feeder (DADF) boosts productivity as it eliminates the need to manually change the pages of your original document:

- Faxing: 2-sided faxes can be conveniently sent and received
- · Copying: Just like a stand-alone copier, 1 or 2-sided documents can be made into 2-sided copies. Alternatively, 2-sided documents can be converted to 1-sided copies
- · Colour Scanning: 2-sided documents can be easily scanned using the DADF, so you do not have to flip pages manually



MFC-8860DN's unique Automatic Duplex definitely provides greater cost savings in the long run.

Printing - Professional Results at Rapid Speeds

Keep up to speed with impressive print speeds of up to 28ppm for A4 and up to 30ppm for Letter while maintaining high quality print resolutions. Even as your printing demands increase, you'll be fully prepared as the memory and paper capacity are easily upgradeable.

- True 1,200dpi print resolution
- Memory upgradeable from 32MB up to 544MB[†]
- Standard 250-sheet paper tray and 50-sheet multi-purpose tray, expandable with optional 250-sheet paper tray[†]



Faxing - Intuitive Controls and Convenience

Fax communications are swift and easy with the 33.6K bps fax modem that transmits in as little as 2 seconds* per page. Its features are designed for your convenience, such as speed dialling for frequently used numbers and out-of-paper reception to store more incoming faxes.

- Up to 40 one-touch dials and 300 speed dial locations
- Up to 500-page* out-of-paper reception
- Unique PC Fax Receive**
 - Incoming faxes are stored in the memory even when the PC is switched off. These faxes will be transferred from the MFC's memory to the PC the next time it is switched on. You can then choose to store your faxes as soft copy or delete them altogether, saving on paper and toner.
 - Faxes can be received in soft copy to a designated PC via a local or network connection, allowing for easy management of faxes
- Fax Receive (RX) Stamp feature for tracking of documents
- Fax Forward feature where incoming faxes can be forwarded to your email address, thus increasing your mobility and keeping you up-to-date with faxes even while travelling.



 4-Day Memory Battery Backup ensures faxes in memory will not be lost and that your fax journal and user settings are still intact, in case of power failure.



- * ITU-T Test Chart, Standard Resolution
- ** Applicable for Windows® only. Function in monochrome only

Fast & Superior Copying

Get the ideal mix of efficiency and quality with rapid copying speeds of up to 28cpm and resolutions of up to 1,200 x 600dpi for the professional edge you require.

- Scale your copies conveniently from 25% to 400% in 1% increments
- 2 or 4 pages can be copied onto one A4 sheet to save paper



Vibrant Scanned Images

Despite its monochrome laser technology, the machine is able to scan in full colour, and comes with intelligent management software tool (ControlCenter2) that has a wide range of control features including user-customisation buttons for ease-of-use.

- TWAIN compliant i.e. ideal for scanning graphics
- Scan directly to Image, OCR, File, Email as an attachment or to FTP server



Effortless Connectivity Setup

MFC-8860DN's dual ports enable flexible connectivity to any office, via USB 2.0 or Parallel interface. In addition, it comes complete with network applications, enabling your workgroup to share the Print, Scan and PC Fax functions.



Easy Network Integration

The embedded Network Management Tools give you complete control of your networked environment. This includes BRAdmin Professional Software for administering LAN connected devices, Web BRAdmin for the WAN and e-mail notification that alerts administrators or users whenever an error occurs.




For greater flexibility, MFC-8860DN supports IPv4 and IPv6. With LDAP (Lightweight Directory Access Protocol), the MFC-8860DN can search for fax numbers and e-mail addresses of users from externally administered LDAP servers. This saves time from the manual input of users' information into the MFC.

Security

MFC-8860DN comes with a secure print feature which allows users to send confidential documents in secure mode.

To provide even greater control over document security, this model also comes with a Secure Function Lock. It allows an administrator to restrict user access to certain functions like printing, faxing, copying and scanning.




Cost Efficient Supplies

To help you save on running costs, MFC-8860DN comes with a separate toner cartridge and drum. Now, you do not have to throw away a still usable drum when your toner is exhausted – a saving that any user will appreciate.

Taking savings another step further is the Toner Save feature. When activated, it allows you to save toner, reducing the frequency of cartridge replacement.







Specifications

General		
Technology		Laser
LCD Display		22 characters x 5 lines with luminated backlight
Memory Backup		Yes - Up to 4 days
Function Lock		Yes - restricts public access to certain functions
Setting Lock		Yes
Memory	Standard	32MB
	Optional	Expandable up to 544MB [†] (one 144-pin DIMM slot)
Paper Capacity	Multi-Purpose Tray	Up to 50 sheets
(Based on 80gsm)	Standard Input Tray	Up to 250 sheets
	Optional Input Tray	Up to 250 sheets (LT-5300) [†]
	Output Tray	Up to 150 sheets, face down
Automatic Document		Up to 50 sheets
Feeder (ADF)		
Media Types	Multi-Purpose Tray	Plain Paper, Bond paper, Recycled Paper, Envelopes, Labels
		and Transparencies
	Standard Input Tray	
	Optional Input Tray	Plain Paper, Bond paper, Recycled Paper
Media Weights	ADF	64 – 90gsm
	Multi-Purpose Tray	60 – 161gsm
14 " 0"	Paper Tray	60 – 105gsm
Media Sizes	ADF	Width 148-215.9mm , Length 148-355.6mm
	Multi-Purpose Tray	Width 69.9-215.9mm , Length 116-406.4mm
		A4, Letter, B5(ISO), A5, B6, A6, Exe
Circultananus Onesation	Optional Input Tray	A4, Letter, B5(ISO), A5, B6, Exe
Simultaneous Operation		(Print/Fax) (Print/Scan) (Print/Copy) (Fax/Copy)
Laser Printing		
Print Speed	A4 / Letter	Up to 28ppm / 30ppm
Dist Develope	Auto Duplex Printing	
Print Resolution		Up to true 1,200 x 1,200dpi
First Print Out Time (FPOT)		Less than 8.5 secs
Emulation		PCL®6 and BR-Script 3 (Post Script 3 emulation), IBM Pro-Printer XL, Epson FX-850
Secure Printing		Yes
Resident Fonts	PCL	66 scalable fonts, 12 bitmap fonts (Letter Gothic 16.66, OCR-A,
riesident ronts	I OL	OCR-B), 11 bar codes
	BR-Script	66 scalable fonts
Printer Drivers	Битовира	Win 98/SE) / Me and NT4.0 / 2000 / XP Driver with Auto
Times Birroro		Installer Program, Mac OS 9.1 - 9.2/ OS X 10.2.4 or greater
Laser Faxing		inclaid Frogram, was seed in the seed to be in the greater
Modem Speed		Super G3 33.6K bps, approximately 2 sec**
Coding Method		MH / MR / MMR / JBIG
Auto Duplex Faxing		Yes, for both fax sending and receiving
Fax / Tel Switch		Automatic recognition of fax and telephone reception (Hook Key)
Automatic Redial		Automatic redial if the recipient fax is busy
One-Touch Dials		Up to 40 locations
Speed Dials		Up to 300 locations
Group Dials		Up to 20 groups
Broadcasting Locations		Up to 390 locations
Quick Scan (Memory Transmission)	A4 & Letter	Approximately 2 sec per page
Auto Reduction		Automatically reduces a received fax to fit onto a single sheet of A4
Error Correction Mode (ECM)	Ensures received documents are error-free
Error Re-Transmission		Yes
Super Fine		Enables quality transmission and reception of very small print or
		line drawings
Grey Scale		256 levels of colour
Memory Transmission		Up to 500 pages**
Out-of-Paper Reception		Up to 500 pages**
Fax Forwarding		Yes
Fax Forwarding Broadcast		Yes

For more information regarding Systems Requirements, please visit http://solutions.brother.com

- † Requires separate purchase

 1 3 sides per minute, 6,5 sheets per minute

 "ITJ = 11 Chair Standard Resolution

 "Depends on availability in the individual countries

 "Depends on availability in the individual countries

 "Supported OS Versions under Network are Virndows® 98(SE) / Me / 2000 Professional / NT® 4.0 (For PC-Print, Scan-to-FTP/PaperPort® & PC-Fax Sand only); 78/7 XP Professional x84 Edition, as well as Macintosh® OS 9.1 9.2 (For PC-Print, Scan-to-FTP & PC-Fax Send only), OS X 10.2 4 or greater

Fax Retrieval		Yes	
Remote Access		Yes – from another touch tone phone	
Enhanced Remote Activate		Yes	
Dual Access		Yes	
Delayed Timer		Yes – Up to 50 faxes	
Polling		Yes - Up to 50 sheets, available for sending and receiving	
Lists / Reports		Activity Report, Journal Report, Transmission Verification Report,	
		Coverpage, Caller ID List***, Help List, Tel Index List (Numeric &	
		Alphabetic), System Setup (User Setting) List, Order Form	
Laser Copying			
Copy Speed	A4 / Letter	Up to 28cpm / 30cpm	
Auto Duplex Copying		Yes	
Copy Resolution		Up to 1,200 x 600dpi	
First Copy Out Time (FCOT)		Less than 10.5 secs (From READY mode)	
Multi Copy	Stack	Yes – Up to 99 copies	
Multi Copy	Sort	Yes - Sort output copies as desired	
Reduction / Enlargement Ratio		25% - 400% in 1% increments	
N in 1 Printing	A4 / Letter only	Compress 2 or 4 pages onto a single sheet	
Poster Printing	A4 / Letter only	Enlarge an image to print on 3 x 3 pages	
Colour Scanning			
Scanning Resolution	Optical	Up to 600 x 2,400dpi	
oca ming nesolution	Interpolated	Up to 19,200 x 19,200dpi	
Auto Duplex Scanning	interpolated	Ves	
Grey Scale		256 shades of grey	
Colour Depth		48 / 24 bit colour processing	
Document Scanning Width		Up to 210mm	
"Scan" Key		Scan to Image / OCR / Email / File / FTP	
		ocarto image/ oort/ Email/ File/ Fil	
Mono PC Faxing			
Sending		Yes, available for Windows® and Macintosh®	
Receiving		Yes, available for Windows® only – Works even when PC is switched off	
Manual Broadcasting		Up to 50 locations	
Interface(s)			
External TAD Interface		Interface for connecting external telephone answering device	
Host Interface		IEEE1284 Parallel and Hi-Speed USB 2.0	
Network Interface****		10/100Base-TX Ethernet Network	
Dimensions & Weight			
Dimensions	WxDxH	531 x 450 x 475mm	
Weight		16.7kg	
Consumables (Based on A4/Letter Page @ 5% coverage)			
Toner - Standard Yield	TN-3145	Up to 3,500 pages	
- High Yield	TN-3185 [†]	Up to 7,000 pages	
Drum	DR-3115	Up to 25,000 pages (1 page per job)	
Other Information			
	Windows®	Win 98(SE) / Me and NT4.0 / 2000 / XP / XP Professional x64 Edition	
Supported OS Versions	Windows® Macintosh®		
	IVIACII ILUSI I	Mac OS 9.1 - 9.2, Mac OS X 10.2.4 or greater (Simple Network Configuration is supported with OS X 10.2.4 or greater)	
Bundled Software	Windows®	Brother MFL-Pro Suite	
Duriuleu SuitWale	**IIIUUWS®	Brother ControlCenter2	
		ScanSoft® PaperPort® with OCR	
	Macintosh®	Presto!® PageManager®	
Supported Protocols	IPv4	ARP, RARP, BOOTP, DHCP, APIPA(Auto IP), ICMP, WINS/NetBIOS,	
Supported Protocols	IFV4	DNS, mDNS, LPR/LPD, Port9100, IPP, FTP, SNMP, HTTP,	
		TELNET, POP3/SMTP, TFTP, LDAP	
	IPv6	ICMPv6, NDP, DNS, mDNS, LPR/LPD, Port9100, IPP, FTP, SNMP,	
	IFVO		
Notwork Management Table		HTTP, TELNET, POP3/SMTP, TFTP, LDAP	
Network Management Tools		BRAdmin Professional Web Record Management	
		Web Based Management	
Internal Fee		BRadmin Light	
Internet Fax		Yes – allows documents to be transmitted over the LAN or Internet	
LDAD		to other Internet fax machines	
LDAP		Yes – allows you to search for fax numbers and email addresses	
D O	01	from your server	
Power Consumption	Sleep	Average 17W	
	Standby	Average 85W	



Average 1,104W











Brother International (NZ) Limited